

DRA-OI NYLON SELF-DRILL FIXING FOR DRYWALL



TECHNICAL FEATURES





• APPLICATION:


- Ideal for installation of sockets, light switches and other electrical fittings
- Shelves and bathroom accessories on standard plasterboard.
- Installation of ceiling fixtures, such as light fittings
- Fixing light shelving, brackets and hooks

• FEATURES:

- Flange prevents accidental push through in plasterboard.
- Can be used in single and double thickness plasterboard.
- Short length ideally suited for dry lined walls.
- Installation with a standard screwdriver means that no special tools are necessary.
- Recommended screw diameter: 3.5 4.2 mm

MATERIAL:

Plug: Nylon (PA6)



Pl	ug	Scr	ew	Fixture	
Diameter	Length	Diameter	Length	Max. thickness	Hole diameter
d	ι	D	L	t _{fix}	d _f
[mm]					
14	22	-	-	-	-
14	22	3.9	32	12	5
	Diameter d	Diameter Length d l	Diameter Length Diameter d I D [m] 14 22 -	Diameter Length Diameter Length	Diameter Length Diameter Length Max. thickness

Installation data

Size			DRA-01(PLUS)
Fixing diameter	d	[mm]	14
Min. substrate thickness	h _{min}	[mm]	9.5
Min. installation depth	h _{nom}	[mm]	9.5
Min. spacing	S _{min}	[mm]	22
Min. edge distance	C _{min}	[mm]	22

Basic performance data

Substrate		Plasterboard min. 9.5 mm	Plasterboard min. 12.5 mm		
CHARACTERISTIC LOAD F _{Rk}					
DRA-01 (PLUS)	[kN]	0.23	0.25		
DESIGN LOAD F _{Rd}					
DRA-01 (PLUS)	[kN]	0.09	0.10		
RECOMMENDED LOAD F _{rec}					
DRA-01 (PLUS)	[kN]	0.06	0.07		

ACCESORIOS DISCOS METÁLICAS FIJACIONES QUÍMICAS ABRAZAI SOPORTACI S·MÁQUINA DE GAS · HERRAMIENTAS · BRIDAS DE NYLON :OS · METÁLIC NES BRAZADERAS DE NYLON : TACOS : SOPORTACIÓN : ANCLA RAMIENTAS **TORN** ÍA Y ACCESORIOS · DISCOS · METÁLICAS · FIJACIONES QUÍN AZADERAS D CIÓN·ANCLAJES·BROCAS· MÁQUINA DE GAS· HERRAMIE DAS DE NYLON : OS · DISCOS · METÁLIC MICAS · ABRAZADO OS · SOPORTACI MÁQUINA DE GAS · H AS DE NYLON · :OS · METÁLICA ABRAZADERAS DE NYLON·TACOS · SOPORTACIÓN · ANCLA RAMIENTAS · RÍA Y ACCESORI SISTEMAS DE FIJACIÓN CIONES QUÍN AZADERAS DE N **TACOS** RTACIÓN · ANCLAJES · BROCAS · MÁQUINA DE GAS · HERRAMIE റ DE NYLON : TORNITLERÍA Y ACCESORIOS : DISCOS : METÁLICAS : FIJACIONES QUÍMICAS : ABRAZADO

DRA-02 METAL SELF-DRILL FIXING FOR DRYWALL



TECHNICAL FEATURES



APPLICATION:

- Fixing electrical boxes, sanitary ware, cable trunking, etc.
- Shelves and bathroom accessories on standard plasterboard
- Ideal for installation of sockets, light switches and other electrical fittings
- · Fixing light shelving, brackets and hooks
- Timber or metal battens

• FEATURES:


- Recommended for fire resistant aplication.
- Flange prevents accidental push through in plasterboard.
- Can be used in single and double thickness plasterboard.
- Short length ideally suited for dry lined walls.
- No drill required simply pierce paper skin and screw home.
- Ideal for use with either a power or manual Pozidriv screwdriver.


• MATERIAL:

Plug in Metal



Product information





Installation data

Size			DRA-02 (PLUS)
Fixing diameter	d	[mm]	13
Min. substrate thickness	h _{min}	[mm]	9.5
Min. installation depth	h _{nom}	[mm]	9.5
Min. spacing	S _{min}	[mm]	35
Min. edge distance	C _{min}	[mm]	35

Basic performance data

Substrate		Plasterboard min. 9.5 mm	Plasterboard min. 12.5 mm		
CHARACTERISTIC LOAD F _{Rk}					
DRA-02 (PLUS)	[kN]	0.15	0.19		
DESIGN LOAD F _{Rd}					
DRA-02 (PLUS)	[kN]	0.06	0.08		
RECOMMENDED LOAD F _{rec}					
DRA-02 (PLUS)	[kN]	0.04	0.06		